

- Floor Type Electrode Oven designed for **Re-Baking, Re-Conditioning** and **Holding** of welding electrode for high quality weld with build in adjustable thermostat controlled with digital temperature display.
- **PID MICRO-PROCESSOR POWER CONTROLLER.**
- All ovens are fitted with high temperature door gasket to prevent heat loss.

MILD STEEL BODY
E 060M / E 120M



STAINLESS STEEL BODY
E 060S / E 120S



Model	E 060M / E 060S	E 120M / E 120S
Capacity (Rod Lght. 450mm)	60 kgs (+/-)	120 kgs (+/-)
Temperature Range (Average Stabilized)	30°C ~ 400°C (86°F ~ 752°F)	30°C ~ 400°C (86°F ~ 752°F)
Input Voltage 50/60Hz	1ph, 220-240VAC	1ph, 220-240VAC
Input Power	900W	1800W
External Dimension (H x D x W)	620 x 735 x 436 mm	790 x 735 x 436 mm
Internal Dimension (H x D x W)	210 x 500 x 280 mm	375 x 500 x 280 mm
Body Insulation (Ceramic wool)	75 mm	75 mm
Weight	45 kgs	57 kgs



STAINLESS STEEL BODY
E 200S / E 300S
E 400S / E 600S

MILD STEEL BODY
E 200M / E 300M
E 400M / E 600M
E 1000M



TIMER Option : (0 -10hr)

Timer changeover baking temperature to holding temperature controller continuously when time expires. This option saves energy and reduces oxidation to electrode. Holding temperature range from 0 to 300°C.

Model	E 200M / E 200S	E 300M / E 300S	E 400M / E 400S	E 600M / E 600S	E 1000M
Capacity (Rod Lght. 450mm)	210 kgs (+/-)	300 kgs (+/-)	400 kgs (+/-)	600 kgs (+/-)	1000 kgs (+/-)
Temperature Range (Average Stabilized)	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F	30°C ~ 400°C 86°F ~ 752°F
Input Voltage 50/60Hz	1ph, 220-240VAC	1ph, 220-240VAC	3ph, 380-440 VAC	3ph, 380-440 VAC	3ph, 380-440 VAC
Input Power	2700W	2700W	5300W	6600W	7900W
External Dimension (H x D x W)	960 x 735 x 620 mm	1115 x 735 x 620 mm	1140 x 755 x 905 mm	1440 x 787 x 910 mm	1700 x 787 x 1060 mm
Internal Dimension (H x D x W)	505 x 500 x 455 mm	650 x 500 x 455 mm	650 x 500 x 695 mm	950 x 500 x 695 mm	1200 x 500 x 810 mm
Body Insulation (Ceramic wool)	75 mm	75 mm	100 mm	100 mm	100 mm
Weight	86 kgs	96 kgs	168 kgs	217 kgs	242 kgs