

- Portable Type Electrode Oven designed for **Re-Baking, Re-Conditioning** and **Holding** of welding electrode for high quality weld with build in temperature gauge & adjustable thermostat controller.

Model	P 030M
Capacity (Rod Lght. 450mm)	30 kgs (+/-)
Temperature Range (Average Stabilized)	50°C ~ 300°C (Analog) (122°F ~ 572°F)
Input Voltage (Heating Element)	1phase, 220-240VAC - 50/60hz (900 w)
External Dimension (H x D x W)	755 x 410 x 480 mm
Internal Dimension (H x D x W)	500 x 200 x 200 mm
Body Insulation (Ceramic wool)	50 mm
Net Weight	27 kgs



P 30M



P 05A/P 05D

P 10A/P 10D

P 25A/P 25D

- Portable Type Electrode Oven designed for **Holding** of welding electrode to keep it constantly warm.
- The unit uses **Tubular Heating Element** for greater heating efficiency and reliability.
- Provide constant heating temperature.

Model	P 05A	P 05D	P 10A	P 10D	P 25A	P 25D
Capacity (Rod Lght. 450mm)	5 kgs (+/-)	5 kgs (+/-)	10 kgs (+/-)	10 kgs (+/-)	25 kgs (+/-)	25 kgs (+/-)
Temperature Range	150°C (302°F)	150°C (302°F)	150°C (302°F)	150°C (302°F)	130°C (266°F)	130°C (266°F)
Input Voltage 50/60Hz	220-240VAC	DC 80-110V	220-240VAC	DC 80-110V	220-240VAC	DC 80-110V
Input Power	160W	160W	160W	160W	160W	160W
External Dimension (H x D x W)	150 x 175 x 630	150 x 175 x 630	172 x 200 x 625	172 x 200 x 625	585 x 255 x 220 mm	585 x 255 x 220 mm
Internal Dimension (H x D x W)	76 x 76 x 500	76 x 76 x 500	100 x 100 x 500	100 x 100 x 500	500 x 145 x 145 mm	500 x 145 x 145 mm
Body Insulation (Rock Wool)	25mm	25mm	25mm	25mm	25mm	25mm
Weight	5.0 kgs	5.0 kgs	6.0 kgs	6.0 kgs	11.0 kgs	11.0 kgs