

**TEM Model - Torque Tester**

- Accuracy: 0.5% in 10% -100% of full load
- Convenient operation menu
- 7 inch colorful touch screen
- Three modes: Random, Peak, First Peak
- All popular torque Units can be selected: N.m ; cN.m ; kgm ; ckgm ; Lb.ft ; Lb.in ; Oz.in
- Automatic return to zero
- Overload warning signal
- Languages available: Chinese or English
- Calibration period reminder
- Stores up to 5000 readings
- Automatic shutdown function



Item No.	Square Drive	Torque Range		Out Diameter mm	Height mm	Weight kg
		N.m	Lb.ft			
TEM225	3/8"	2.5-25	1.8-18	102	77	2.3
TEM240	3/8"	4.0-40	3.0-30	102	77	2.33
TEM275	3/8"	7.5-75	5.5-55	102	77	2.37
TEM3150	1/2"	15-150	11-110	102	77	2.44
TEM3250	1/2"	25-250	18.4-184	102	77	2.52
TEM3400	1/2"	40-400	29.5-295	102	77	2.44
TEM4650	3/4"	65-650	48-480	136	103	2.54
TEM41250	3/4"	125-1250	92.2-922	136	103	2.73
TEM52500	1"	250-2500	184.5-1845	136	103	3.01

Note: Due to the product improvement, the technical parameters are subject to variation, please refer to the actual production from the factory.