



(Length comparison)



GS Series Mini Micrometer Adjustable (Click) Torque Wrench


- Accuracy: $\pm 4\%$ in clockwise direction from 20% to 100% of capacity.
- Small sizes and light weight, and can be operated in confined spaces.
- Permanently stamped major and minor scales for precision torque values setting.
- Minor scale is 1/10 of increment of main scale.
- Set torque by locking ring. The rebound self-locking structure can reliably lock the required torque.
- Grooved non-slip grip fits comfortably in your hand.
- Various kinds of heads designed for different applications:
 - GSM_S / GS_S model: Reversible ratchet head, fine-tooth ratchets suitable for operation in confined spaces requiring only 8 degrees swing.
 - GSMH_S / GSH_S model: Head holder for standard 9x12mm rectangular shank heads.
 - GSMR_S / GSR_S model: Round head holders for $\Phi 12\text{mm}$ heads.




Torque Locking



1 Pull and hold the locking ring



2 Rotate the tube to adjust the torque by the other hand



3 Release the locking ring after torque being set

GSM_S Model

Reversible Ratchet Head Torque Wrench
Both directions, 8° swing suitable for confined space

GS_S Model (English Unit)



Metric

Item No.	Square Drive	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
GSM15S	1/4"	1-5	0.05	183	28	0.3
GSM110S	1/4"	2-10	0.1	195	28	0.32
GSM115S	1/4"	3-15	0.15	207	28	0.33
GSM125S	1/4"	5-25	0.25	230	28	0.35
GSM240S	3/8"	8-40	0.4	260	36	0.37
GSM260S	3/8"	10-60	0.5	310	36	0.51

English

Item No.	Square Drive	Torque Range Lb.in	Increment Lb.in	Length mm	Width mm	Weight kg
GS150S	1/4"	10-50	0.5	183	28	0.32
GS1100S	1/4"	20-100	1	195	28	0.34
GS1150S	1/4"	30-150	1.5	207	28	0.36

GSMR_S Model

Round Head Holder Torque Wrench
For round hole inserts

GSR_S Model (English Unit)



Metric

Item No.	Round Hole mm	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
GSMR125S	φ 12	1-5	0.05	167	28	0.28
GSMR1210S	φ 12	2-10	0.1	179	28	0.28
GSMR1215S	φ 12	3-15	0.15	191	28	0.3
GSMR1225S	φ 12	5-25	0.25	214	28	0.32
GSMR1240S	φ 12	8-40	0.4	244	28	0.34
GSMR1260S	φ 12	10-60	0.5	278	28	0.39

English

Item No.	Shank Size mm	Torque Range Lb.in	Increment Lb.in	Length mm	Width mm	Weight kg
GSR1250S	φ 12	10-50	0.5	167	28	0.28
GSR12100S	φ 12	20-100	1	179	28	0.28
GSR12150S	φ 12	30-150	1.5	191	28	0.3

GSMH_S Model

Rectangular Shank Head Holder Torque Wrench
For rectangular shank head inserts

GSH_S Model (English Unit)



Metric

Item No.	Shank Size mm	Torque Range N.m	Increment N.m	Length mm	Width mm	Weight kg
GSMH95S	9x12	1-5	0.05	167	28	0.28
GSMH910S	9x12	2-10	0.1	179	28	0.3
GSMH915S	9x12	3-15	0.15	191	28	0.31
GSMH925S	9x12	5-25	0.25	214	28	0.33
GSMH940S	9x12	8-40	0.4	244	28	0.36
GSMH960S	9x12	10-60	0.5	278	28	0.41

English

Item No.	Shank Size mm	Torque Range Lb.in	Increment Lb.in	Length mm	Width mm	Weight kg
GSH950S	9x12	10-50	0.5	167	28	0.28
GSH9100S	9x12	20-100	1	179	28	0.3
GSH9150S	9x12	30-150	1.5	191	28	0.32

100% Calibrated

Unique serial number for each torque wrench, corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of "NovaTork" torque products

