



SL Series Slipper Torque Wrench


- Accuracy: $\pm 6\%$ from 20% to 100% of capacity.
- The head part is made of aviation aluminum, the pipe is made of alloy steel, strong and durable.
- SL torque wrench is a preset torque wrench, set the torque value with special tools before use.
- The torque cannot be changed arbitrarily during use, which guarantees the working quality.
- When the preset torque value is reached, it will slip and will not cause overload.
- Stop applying force when you hear the "Click" sound of sliding.
- The ingenious ratchet function makes it easy to tighten clockwise, even in a narrow space.
- Comfortable TPR handle for long time working, suitable for assembly line and production line.



SL Model Slipper Torque Wrench

Ratchet sliding mechanism, avoid overloading


Metric							
Item No.	Square Drive	Torque Range N.m	Length mm	Width mm	Height kg	Weight kg	Adjusting Tool
SL16	1/4"	1-6	200	31	35	0.41	DC.Q6230
SL125	1/4"	3-25	220	38	41	0.51	DC.Q6232
SL260	3/8"	10-60	330	46	49.3	0.82	DC.Q6231
SL3100	1/2"	20-100	460	46	53.5	1.06	DC.Q6231



The dedicated adjusting tool can be purchased separately according to this table.

100% Calibrated

Unique serial number for each torque wrench, corresponding to the certificate of calibration



Shockproof packaging

Specially designed for all series of "NovaTork" torque products

